

Camera Cable T32

MONOCHROME CAMERA CABLE

ahlbergcameras.com/products/cables/camera-cable-t32



The T32 camera cable is used together with Ahlberg monochrome cameras. It is a flexible and strong cable specially designed with Kevlar braid for supporting the camera hanging solely by its cable.

MORE INFORMATION ABOUT CAMERA CABLE T32

APPLICATIONS

- Cable for underwater use or in air together with Ahlberg monochrome cameras

BENEFITS

- A flexible and strong cable
- Can be equipped with a reterminable connector for use in air and a molded connector for underwater use
- Specially designed with Kevlar braid for supporting the camera hanging solely by its cable.

SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Width	12 mm
Minimum Bend Radius, Flexible Installation	80 mm
Outer sheath	PUR, frosted
Color	Black
Weight	0.26 kg/m, 0.175 lbs/ft
Tensile Strength	5000 N
Number of conductors	30 + 2 coaxial

ENVIRONMENTAL TOLERANCES

Radiation Tolerance (total dose)	2 000 000 Gy (200 000 000 rad)
Temperature Rating	-40°C to +80°C (-40°F to +176°F)
Water Tightness	3.5 bar

We reserve the right to alter specifications without prior notice

CAMERA CABLE T32 IMAGES



We reserve the right to alter specifications without prior notice