

CCTV Cable T24

FIRE RESISTANT CCTV CABLE

ahlbergcameras.com/products/cables/cctv-cable-t24



The T24 is a shielded twisted pair cable used in CCTV installations. It is halogen free and flame resistant. The T24 connects the camera/light/microphone/-pan-and-tilt unit with the control unit. The control unit/protocol inverter is usually placed in an adjacent room with a lower degree of radiation.

MORE INFORMATION ABOUT CCTV CABLE T24

APPLICATIONS

- Cable for CCTV use

BENEFITS

- Fire resistant, Category A according to IEC 60332-3-22:2000

SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Width	13 mm
Minimum Bend Radius, Fixed Installation	97.5 mm
Minimum Bend Radius, Flexible Installation	195 mm
Outer sheath	PUR, frosted
Color	Black
Weight	0.26 kg/m, 0.175 lbs/ft
Tensile Strength	5000 N
Number of conductors	23 + 1 coax

ENVIRONMENTAL TOLERANCES

Radiation Tolerance (total dose)	2 000 000 Gy (200 000 000 rad)
Temperature Rating	-40°C to +80°C (-40°F to +176°F)

We reserve the right to alter specifications without prior notice

CCTV CABLE T24 IMAGES



We reserve the right to alter specifications without prior notice